

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS
P. D. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO.           | FILING DATE    | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO.         | CONFIRMATION NO |
|---------------------------|----------------|----------------------|-----------------------------|-----------------|
| 09/474,536                | 12/29/1999     | QINGYU ZENG          | 24707A                      | 2359            |
| 22889 7.                  | 590 08/19/2004 |                      | EXAMINER                    |                 |
| OWENS CORNING             |                |                      | TORRES VELAZQUEZ, NORCA LIZ |                 |
| 2790 COLUMI<br>GRANVILLE, |                |                      | ART UNIT PAPER NUMBE        |                 |
| O14 11 1 1222,            |                |                      | 1771                        |                 |
|                           |                |                      | DATE MAILED: 08/19/200      | 4               |

Please find below and/or attached an Office communication concerning this application or proceeding.

|   |   |   | 11/      |
|---|---|---|----------|
|   | Application No.   | Applicant(s)  |          |
|   | 09/474,536  | ZENG ET AL.   |          |
| Office Action Summary   | Examiner  | Art Unit  |          |
|   | Norca L. Torres-Velazquez   | 1771  |          |
| The MAILING DATE of this communication a<br>Period for Reply  | ppears on the cover sheet with  | the correspondence address  | 5        |
| A SHORTENED STATUTORY PERIOD FOR REP THE MAILING DATE OF THIS COMMUNICATION  - Extensions of time may be available under the provisions of 37 CFR after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a real if NO period for reply is specified above, the maximum statutory perions Failure to reply within the set or extended period for reply will, by state Any reply received by the Office later than three months after the main earned patent term adjustment. See 37 CFR 1.704(b). | N. 1.136(a). In no event, however, may a reply eply within the statutory minimum of thirty (3) od will apply and will expire SIX (6) MONTHS tute, cause the application to become ABANI | be timely filed  0) days will be considered timely.  6 from the mailing date of this commun  DONED (35 U.S.C. § 133). | ication. |
| Status  |   |   |          |
| <ul> <li>1) Responsive to communication(s) filed on 28</li> <li>2a) This action is FINAL. 2b) The Third This action is FINAL. 2b This action is in condition for allow closed in accordance with the practice under</li> </ul>  | nis action is non-final.<br>vance except for formal matters   | •   | its is   |
| Disposition of Claims   |   |   |          |
| 4) ☐ Claim(s) 1-9,11,15-18 and 20-24 is/are pend 4a) Of the above claim(s) is/are withdr 5) ☐ Claim(s) is/are allowed.  6) ☐ Claim(s) 1-9,11,15-18 and 20-24 is/are reject 7) ☐ Claim(s) is/are objected to.  8) ☐ Claim(s) are subject to restriction and  | rawn from consideration.  |   |          |
| Application Papers  |   |   |          |
| 9) The specification is objected to by the Examin 10) The drawing(s) filed on is/are: a) as Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the I  | ccepted or b) objected to by<br>ne drawing(s) be held in abeyance.<br>ection is required if the drawing(s)  | See 37 CFR 1.85(a).<br>is objected to. See 37 CFR 1.  | ` *      |
| Priority under 35 U.S.C. § 119  |   |   |          |
| 12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority docume 2. Certified copies of the priority docume 3. Copies of the certified copies of the priority docume application from the International Bure * See the attached detailed Office action for a list   | ents have been received.<br>ents have been received in Appl<br>riority documents have been receau (PCT Rule 17.2(a)).   | ication No<br>ceived in this National Stag  | e        |
| Attachment(s)   |   |   |          |
| 1) ☑ Notice of References Cited (PTO-892) 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/0 Paper No(s)/Mail Date  | . — .   | mary (PTO-413)<br>ail Date<br>mal Patent Application (PTO-152)  | ı        |

Art Unit: 1771

### **DETAILED ACTION**

## Response to Arguments

1. Applicant's arguments filed May 28, 2004 have been fully considered but they are not persuasive.

a. Applicants argue that the SWAN et al. patent is silent as to an end product having been treated to bond any bi-component polymer binder fibers and primary fibers to themselves and to each other without softening the principal component of the binder fibers.

It is noted that SWAN et al. teach the use of bicomponent binder fibers which are known to have two components and the sheath component (the adhesive polymer) is known to have a lower softening temperature that provides with the type of bonding aimed by applicants. A heating step that will activate this type of fibers is well known in the art in order to produce the bonding by activating the adhesive polymer in the sheath of the bicomponent fiber while the core is the supporting component and has a higher softening temperature. It is the Examiner's position that SWAN et al. does provide the structure claimed herein and the application of a heating step is implied with the use of this type of fibers as binding fibers in a nonwoven web. The Examiner further provides the EP 0538047 A1 reference as evidence to support this position. The EP 0538047 A1 reference is directed to nonwoven material containing bicomponent synthetic fibers having a thermoplastic component with a lower softening point component, such as a sheath-core bicomponent fiber and teaches exposing the fibers to a bonding temperature

Application/Control Number: 09/474,536 Page 3

Art Unit: 1771

sufficiently high to soften the lower softening point component of the bicomponent fibers and to obtain a high-loft nonwoven material through inter-fiber contact points. (Abstract)

b. With regards to new claims 22 and 24, the limitation "in which the primary fibers are polymer fibers other than polypropylene" is not supported by the Specification.

# Claim Rejections - 35 USC § 112

2. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 22 and 24 are rejected under 35 U.S.C. 112, first paragraph, as containing matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. The phrase " in which the primary fibers are polymer fibers **other than polypropylene**" is new matter, because this negative limitation is not literally supported by the specification. *Ex Parte Grasselli*, 231 USPO 393.

### Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 4. Claims 1-9, 15-18, 21 and 23 are rejected under 35 U.S.C. 102(b) as being anticipated by SWAN et al. (US 5,773,375) further evidenced by CAREY et al. and EP 0538047 A1.

Art Unit: 1771

SWAN et al. discloses an acoustical insulation web laminate designed for use in a motorized vehicle that comprises: a) a nonwoven acoustical insulation web 15 comprising thermoplastic melt-blown micro fibers, which is equated to the present "blanket" of fibers, and b) a second layer, which is equated to the present facing material, laminated to the acoustical insulation web to form the laminate, wherein portions of the acoustical insulation web and the second layer can be thermally consolidated to form reduced thickness areas which are of a thin gauge relative to other portions of the laminate. (Column 3, lines 36-45) The reference also teaches that the lamination of film 14 to the web 15 composite can be done by using an adhesive. (Column 6, lines 29-32) SWAN et al. also teaches the use of binder fibers in the web. (Column 4, lines 31-34) Typical binder fibers include bicomponent binder fibers, which have an adhesive component, and a supporting component arranged in a coextensive side-by-side, concentric sheath-core or elliptical sheath-core configuration. The Examiner equates the adhesive component of the bicomponent binder fibers to the binder component polymer component of the present invention and the supporting component of the bicomponent binder fibers to the principal polymer component of the present invention. The melt-blown polypropylene fibers of SWAN et al. are equated to the primary fibers of the present invention. (Column 4, lines 31-56)

The reference further teaches that the thickness of the acoustical insulation web is in the range of about 0.5 cm to about 15 cm, preferably is at least about 2 cm, more preferably at least about 7 cm. (Column 5, lines 23-25) On Figure 4, the reference shows the laminate including a water barrier layer such as a planar thermoplastic film 14 formed of a relatively thin thermoplastic material such as polypropylene. (Column 5, lines 63-67 thru Column 6, lines 1-2). The thickness of the film 14 is in the range of between about 20 microns to about 250 microns.

Art Unit: 1771

(Column 6, lines 6-9). The reference further teaches that the laminate 10 is typically pressure molded in a heated die to form reduced thickness areas 17 along its outer periphery 16, of approximately 508 microns (0.0508 cm) in thickness. The reduced thickness areas 17 promote the integrity of the laminate 10 in those areas and permit the laminate 10 to be easily handled by vehicle manufacturers during assembly operations. (Column 6, lines 35-47) The reduced thickness areas 17 of the SWAN et al. reference are equated to the presently claimed densified perimeter flange.

With regards to claim 4, refer to the exemplary values presented by the Examiner in section 2 of the present office action, which show that the SWAN reference teaches the use of reduced thickness areas ("flanges") with a thickness less than about 15 percent of the thickness of the web ("blanket").

With regards to claims 6-7 and 16-17, SWAN et al. further teaches that the laminate 10 can include an optional scrim layer secured to the web opposite the film. The reference teaches that the optional scrim layer increases the integrity of the laminate. The reference further teaches that a second optional scrim layer can be secured between the film and the web. (Column 6, lines 14-34) Therefore, when the second optional scrim layer is secured between the film and the web, this embodiment will provide the claimed facing material comprising a scrim and a film.

With regards to claims 8 and 18, it is noted that SWAN et al. is silent with respect to the claimed static coefficients of friction. However, it is reasonable to presume that the claimed static coefficient of friction is inherent to the invention SWAN et al. Support for said presumption is found in the use of the same starting materials (i.e. includes meltable binder fibers in addition to melt-blown fibers in the acoustical web and a liquid barrier thermoplastic

Art Unit: 1771

film), like processes of making the articles (i.e., pressure molding), and the production of similar end-products (i.e., acoustical insulation, etc...). The burden is upon the Applicant to prove otherwise. *In re Fitzgerald*, 205 USPQ 594.

With regards to the binder component with a softening point lower than the softening of the principal component, it is noted that SWAN et al. teaches the use of a binder fiber with a sheath-core structure having a core of crystalline polyethylene terephthalate surrounded by a sheath of an adhesive polymer formed from isophthalate and terephthalate esters. (Column 4, lines 53-56) It is well known that crystalline polymers have a higher melting point than adhesive components in a bicomponent fiber. By having a difference in melting point (or softening point) this type of bicomponent fibers can be used as binder or bonding fibers, therefore the difference in softening point is inherent to the bicomponent binder fibers taught by SWAN et al. This is further evidenced by CAREY, Jr. et al. (US 4,837,067) cited by the SWAN et al. on Column 4. lines 49-51. CAREY, Jr. et al. explicitly says that the adhesive component of thermally bonding fibers must be thermally activatable (i.e. meltable) at a temperature below the melt temperature of the structural fibers of a batt. CAREY, Jr. et al. also teaches the use of bicomponent bonding fibers with structures such as a sheath-core. (Column 4, lines 27-42) It is the Examiner's position that SWAN et al. does provide the structure claimed herein and the application of a heating step is implied with the use of this type of fibers as binding fibers in a nonwoven web. The Examiner further provides the EP 0538047 A1 reference as evidence to further support this The EP 0538047 A1 reference is directed to nonwoven material containing position. bicomponent synthetic fibers having a thermoplastic component with a lower softening point component, such as a sheath-core bicomponent fiber and teaches exposing the fibers to a

Art Unit: 1771

bonding temperature sufficiently high to soften the lower softening point component of the bicomponent fibers and to obtain a high-loft nonwoven material through inter-fiber contact points. (Abstract

## Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 11 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over SWAN et al. (US 5,773,375) as applied to claims 1-9 and 15-18 above, and further in view of WEINLE et al. (US 4,840,832).

While SWAN et al. teaches the use of bicomponent binder fibers, it fails to teach the use of polyethylene terephthalate (PET) fibers as the primary fibers and the use of PET in the core and sheath of the bicomponent binder fibers.

WEINLE et al.'s invention is directed to an automobile headliner formed from a batt of polymeric fibers compressed and molded that imparts acoustical and thermal insulation. (Column 1, lines 5-14) The headliner is formed from a batt of polymeric fibers and the polymeric fibers preferably include potentially adhesive binder fibers. (Column 2, lines 9-10) The reference teaches the use of bicomponent fibers having a relatively low melting polymer binder component and a higher melting polymer strength component. (Column 2, lines 15-17) The reference teaches a sheath-core bicomponent construction wherein the core is formed of a relatively high melting polyethylene terephthalate polymer (PET) and the sheath comprises a

Art Unit: 1771

PET co-polymer having a much lower melting temperature. (Column 4, lines 23-28) The polymer fibers, which comprise the batt, are formed of a thermoplastic polymer, such as polyethylene terephthalate (PET). (Column 4 lines 6-7)

Since both, SWAN et al. and WEINLE et al. are directed to acoustical insulation for vehicles, the purpose disclosed by WEINLE et al. would have been recognized in the pertinent art of SWAN et al.

It would have been obvious at the time the invention was made to a person having ordinary skill in the art to modify the acoustical insulation of SWAN et al. and provide it with polyethylene terephthalate fibers to form the batt (or web) and bicomponent fibers with a core of PET and a sheath of PET with the motivation of providing an insulation material with a molded batt of fibers that remains highly deformable and resilient as disclosed by WEINLE et al. (Column 3, lines 56-68).

7. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

Art Unit: 1771

however, will the statutory period for reply expire later than SIX MONTHS from the date of this

final action.

8. Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Norca L. Torres-Velazquez whose telephone number is 571-272-

1484. The examiner can normally be reached on Monday-Thursday 8:00-4:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Terrel Morris can be reached on 571-272-1478. The fax phone number for the

organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Norca L. Torres-Velazquez

Examiner

Art Unit 1771

August 16, 2004

ELIZABETH M. COLE PRIMARY EXAMINER

Page 9